

Häfele Wireless Adjustable Shelf Lighting System

The solution for integrated lighting in adjustable shelves



Elegant and simple solution for providing lighting in spaces with adjustable shelves.

Bus Bar

- > Specially designed brushed aluminum bus bars are inserted into narrow vertical channels, on the side panels of each cabinet or closet section
- > Thin bus bar design allows for two bus bars to be applied back-to-back in a single panel
- > Optional drill bit made specifically for the bus bar channel is available

Power Supply Kit

- > Connects to a Loox driver to deliver a low voltage current to the bus bars
- > Easily installed either on the top or bottom of the cabinet

Adjustable shelf light bars

- > Built with spring loaded contact assembly transferring the current from the bus bar to the light bar, which is routed into the underside of the shelf
- > Light bars use standard silver coloured 1103 profile
- > Customers can order standard light bars or custom length light bars
- > Medium intensity 12V 2065 LED in 3000K or 4000K in 18", 24", 30" or 36" widths
- > High intensity 12V 2068 LED in 3000K or 4000K in 18", 24", 30" or 36" widths
- > Delivered ready to install into a routed shelf channel
- > No additional cables or leads required
- > Light bars are ULc Certified
- > Lifetime: 50,000 hrs

Häfele Wireless Adjustable Shelf Lighting System

The solution for integrated lighting in adjustable shelves

Voltage	LED family	Light intensity	Wattage W/m	Colour temp. (Kelvin)	Light bar length			
					18"	24"	30"	36"
12 V	LED 2065	Medium	4.8	3000K	833.88.978	833.88.979	833.88.980	833.88.981
				4000K	833.88.982	833.88.983	833.88.984	833.88.985
12 V	LED 2068	High	9.6	3000K	833.88.970	833.88.971	833.88.972	833.88.973
				4000K	833.88.974	833.88.975	833.88.976	833.88.977

Note
Min. order: 1 pc

Description	Package Qty	Item No.
Brushed and anodized aluminum bus bar 2337 x 7 x 4.6 mm (92" x 9/32" x 3/16")	20	833.74.996
8mm bus bar router bit	1	001.25.920
1/4" shank bit for bus bar routing	1	001.25.921

Description	Package Qty	Item No.
Power supply kit - drivers and control sold separately	1	833.88.986
Includes: 1 splice block with clips, 2 spring loaded contact connectors with 500 mm (19 11/16") cable and modular clips, 2 mounting brackets, 1 modular power cable, 1 m (39 3/8"), Mounting screws		