

Chain Usage Utilisation de la chaîne



Specifications

Spécification



MAX.

Size		Work Load Capacité de charge	
in.	mm.	lbs	kg
1/4"	6.3 mm	2,600 lbs	1,179
3/8"	9.5 mm	5,800 lbs	2,630
1/2"	12.7 mm	5.1 tons	4,626
3/4"	19.0 mm	11 tons	9,979

Reel / Bobine



MAX.

No.	Size / Taille		Length / Longueur		Descriptions	Work Load Capacité de charge						Box Bte
	in/po	mm	ft.	m.		Vertical		Choker		Basket		
						lbs.	kg.	lbs.	kg.	lbs.	kg.	
505591	1/4"	6.3	4'	1	Wire Rope Sling with loop on both ends Câble d'acier avec boucle aux deux extrémités	1,300 lbs	590	960	435	2,600 lbs	1,180	1
505601	1/4"	6.3	8'	2	Wire Rope Sling with loop on both ends Câble d'acier avec boucle aux deux extrémités	1,300 lbs	590	960	435	2,600 lbs	1,180	1
505611	3/8"	9.5	8'	2	Wire Rope Sling with loop on both ends Câble d'acier avec boucle aux deux extrémités	2,800 lbs	1,270	2,200	998	5,800 lbs	2,630	1
505621	1/2"	12.7	4'	1	Wire Rope Sling with loop on both ends Câble d'acier avec boucle aux deux extrémités	5,000 lbs	2,268	3,798	1,723	5.1 ton	4,626	1
505641	1/2"	12.7	8'	2	Wire Rope Sling with loop on both ends Câble d'acier avec boucle aux deux extrémités	5,000 lbs	2,268	3,798	1,723	5.1 ton	4,626	1
505651	3/4"	19.0	6'	1.5	Wire Rope Sling with loop on both ends Câble d'acier avec boucle aux deux extrémités	5.6 ton	5,080	8,199	3,719	11 ton	9,979	1